

sealed spherical roller bearings

technologie GMBH
 T: +43 7224 22053
 E: office@asw.at
 W: www.asw.at

ASW.at

d mm	D mm	B mm	dyn. Cr KN	stat. Cor KN	weight kg	limiting speed RPM	Fatigue load limit Pu KN	
25	52	23	44,2	44,2	0,31	3600	4,7	BS2-2205-2CS VT143*
25	52	23	44,0	49,0	0,31	3600	4,7	BS2-2205-2CS K VT143*
30	62	25	64,0	60,0	0,34	2800	6,0	BS2-2206-2CS VT143*
35	72	28	86,5	85,0	0,52	2400	9,0	BS2-2207-2CS VT143*
40	80	28	96,5	90,0	0,62	2200	11,0	BS2-2208-2CS VT143*
40	90	38	150	140	1,2	1900	15,0	BS2-2308-2CS VT143*
45	85	28	102,0	98,0	0,66	2000	11,0	BS2-2209-2CS VT143*
50	90	28	104,0	108,0	0,70	1900	13,0	BS2-2210-2CS VT143*
55	100	31	125,0	127,0	1,00	1700	18,0	BS2-2211-2CS VT143*
60	110	34	156,0	166,0	1,30	1600	20,0	BS2-2212-2CS VT143*
60	110	34	156,0	166,0	1,30	1600	20,0	BS2-2212-2CS K VT143*
65	120	38	193,0	216,0	1,60	1500	28,0	BS2-2213-2CS VT143*
65	120	38	193,0	216,0	1,60	1500	28,0	BS2-2213-2CS K VT143*
70	125	38	208,0	228,0	1,80	1400	26,0	BS2-2214-2CS VT143*
75	130	38	212,0	240,0	2,10	1300	26,5	BS2-2215-2CS VT143*
75	130	38	212,0	240,0	2,10	1300	26,5	BS2-2215-2CS K VT143*
80	140	40	236,0	270,0	2,40	1200	32,0	BS2-2216-2CS VT143*
85	150	44	285,0	325,0	3,00	1100	38,0	BS2-2217-2CS VT143*
90	160	48	325,0	375,0	3,70	1000	46,0	BS2-2218-2CS VT143*
100	180	55	425,0	490,0	5,50	850	65,0	BS2-2220-2CS5 VT143*
110	200	63	560,0	640,0	7,60	640	63,0	BS2-2222-2CS5 VT143*
120	215	69	630,0	765,0	9,75	750	73,5	BS2-2224-2CS5 VT143*